

D1 - Comando a pulsante - *Push-button control*



Articolo Article		W <small>min. max.</small>	V	Hz	LPH <small>mm</small>		Codice Code
CN/63D1N/12/8x22P	■	10÷60	240	50	18x62x12	50	V2512000011
CII/63D1N/12/8x22P	☒	10÷60	240	50	18x62x12	50	V2512000007

Varialuce indissolubilmente collegato al cavo per lampade ad incandescenza ed alogene. Tecnologia MOSFET

Comando a pulsante:

- Pressione breve on-off
- Pressione prolungata regolazione con stop al minimo e al massimo.
- La memoria incorporata consente di mantenere l'intensità luminosa impostata anche in assenza di rete.
- Con spia luminosa per individuazione al buio.
- Fusibile di protezione non sostituibile incorporato.
- Durata della lampada prolungata grazie all'accensione graduale.
- Assenza di ronzio.
- **Fornito esclusivamente cablato con spina Europea e lunghezza 2 metri.**

In line not rewirable for incandescent or halogen bulbs. MOSFET technology

Dimmable by pressure operated micro switch:

- Short push on-off
- Continuous push for regulation, stop at minimum and maximum.
- Internal memory maintains the last light level in absence of mains voltage.
- Provided with line indicator lamp.
- Not replaceable built-in fuse protection.
- Extended bulb life due to soft start.
- No buzzing.
- **Available only as a cordset with Euro plug and 2 meters length.**

