

 ${\tt LED\ TECHNOLOGY>Flexible\ Led\ Strips\ and\ accessories>Flexible\ Led\ Strips\ IP62-IP63}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224145

Flexible Led strip5m SMD2835-180led/m. IP62 24V 14,4W/m - 72W 5000K

May 25th, 2024, 18:28



DESCRIPTION

Flexible constant voltage LED strip D2835 180leds / m 24VDC 72W cold white 5000K. Supply voltage (Vdc) 24V. Total maximum current (A) 3. Power 14.4W / m; total 72W. Luminosity 1296Lm / meter; total 6480Lm. Total length 5 meters. Total number of LEDs 900. Divisible into modules of 6 LEDs every 5cm (one LED every 8.3mm). Degree of protection IP62 for humid environments. Adhesive application on the back. Parallel connection. White PCB color.

PRICE

| Lot | P.V.P. excluding VAT |
|-----|----------------------|
| 1 | 57,46€ |
| 5 | 52,26€ |
| 10 | 49,73€ |



Continued on next page >>



 ${\tt LED\ TECHNOLOGY > Flexible\ Led\ Strips\ and\ accessories > Flexible\ Led\ Strips\ IP62-IP63}}$ ${\tt Flexible\ Led\ Strips\ IP62-IP63\ 24V}$

LFD224145

Flexible Led strip5m SMD2835-180led/m. IP62 24V 14,4W/m - 72W 5000K

TECHNICAL SPECIFICATIONS

SYMBOLS CERTIFICADOS

















Weight: 204 Grams Packging: Roll 5 Meters

NOTES

Total number of led 900. Divisible in modules of 6 Led each 3,3cm, (one led every 5,6mm). With adhesive

OTHER FEATURES

Length (mm): 5000 Width (mm): 10

High (mm): 3 Colour: White PCB

Voltage In (Vdc): 24 Intensidad In (A): 2

Power (W/m): 14.4 Temperature (°C): -20+50

Room Temperature (°C): -20~+50 Colour Temperature (ºK): 5000

Lumen/meter: 1296 Angle ($^{\circ}$): 120

CRI (≥): 80 Life (Hours): 50000

Ingress Protection: IP62 Dimmable: SI

DOCUMENTS

Data Sheet

L CE

UR (USA)