

LUE57088302F2

Led Cob EDC / 57C / 8W / 830 / 230V / F201

May 18th, 2024, 20:54



DESCRIPTION

Led module COB series F2 direct to mains. Dimmable with leading and trailing edge dimmers. Efficiency > 0.95. THD < 30%. Mounting holes according to Zhaga standard. Complying SLR. SVM < 0.1. Pst < 0.4. Flicker free.

PRICE

	Lot	P.V.P. excluding VAT
	1	15,44€
	5	12,87€
	50	11,70€
	100	11,14€

Continued on next page >>

LED TECHNOLOGY > Led modules > Led Lumens Modules
EggDrop F2-series Flicker Free

LUE57088302F2

Led Cob EDC / 57C / 8W / 830 / 230V / F201

TECHNICAL SPECIFICATIONS

SYMBOLS



(EMC)

(LVD)

Weight: 9 Grams

NOTES

ECO design according to ERP directives.. Automatic connectors. Dimmables by leading and trailing edge dimmers. Zhaga standard

OTHER FEATURES

High (mm): 7,6

Voltage In (Vac): 230

Power (W): 8

Room Temperature (°C): -40~+85

Colour Temperature (°K): 3000

Angle (°): 120

CRI (≥): 80

Dimmable: Corte inicio o fin de fase

Diameter (mm): 57

Frecuency (Hz): 50~60

Temperature (°C): -40+85

Critical Temperature (°C): 85

Lumen: 880

Energy efficiency: F

Life (Hours): 50000

Power factor: >0,95

DOCUMENTS

 [Data Sheet](#)

 [EPREL Datasheet](#)

 [Led Cob EDC / 57C / 8W / 830 / 230V / F201](#)

 [Electromagnetic compatibility](#)

 [LVD \(DIRECTA BAJO VOLTAJE\)](#)