

GTC15350 - 122290

Led Driver CC ECO 15-350 350mA 15W

May 25th, 2024, 18:19



DESCRIPTION

Led power supply for independent use at constant current 350mA. The output voltage ranges from 32 to 42V and the power range is from 11.2 to 14.7W. Class II. Protection against open circuit, short circuit, over load and over temperature. Efficiency > 83%. Warranty 7 years (3% failure ratio) 10 years (5% failure ratio). TCI Code 122290

PRICE

	Lot	P.V.P. excluding VAT
	1	6,88€
	5	6,25€
	10	5,68€
	50	5,27€

Continued on next page >>

LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current
Electronic Led Power Supplies 350mA

GTC15350 - 122290

Led Driver CC ECO 15-350 350mA 15W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



Weight: 115 Grams

NOTES

ECO ERP Directives. 350mA constant current power supply.

OTHER FEATURES

Length (mm): 115

High (mm): 29

Voltage Out (Vdc): 32~42

Frequency (Hz): 50~60

Room Temperature (°C): 0~+50

Ingress Protection: IP20

Power factor: 0.9

Width (mm): 45

Voltage In (Vac): 220~240

Intensidad Out (A): 0.35

Power (W): 11.2~14.7

Critical Temperature (°C): 75

Dimmable: NO

DOCUMENTS

 [Data Sheet](#)

 [Led Driver CC ECO 15-350 350mA 15W](#)

 [CB](#)

 [CE](#)

 [ENEC \(Netherlands\)](#)

 [Regulatory Compliance Mark for Australia](#)

 [UKCA](#)