

LUL14048301

Led Lineal LNM14030/4.5W/830/120/C

May 25th, 2024, 14:44



DESCRIPTION

Direct to network Led module. Connectable to each other up to a max of 270W. Dimmable with most dimmers with phase start or end cutoff. Version 120V (UL) and 230V (CE). Color temperatures from 2700K to 6000K. Optionally with CRI80 or CRI 90. Circuit with temperature protection at 150°C and overvoltage.

PRICE

	Lot	P.V.P. excluding VAT
	1	10,14€
	20	9,23€
	200	8,84€

Continued on next page >>

LUL14048301

Led Lineal LNM14030/4.5W/830/120/C

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



(EMC)

(LVD)



Weight: 15 Grams

Packging: Box 100 Units

NOTES

Automatic connectors. Dimmable with most Triac dimmers. SDCM 3

OTHER FEATURES

Length (mm): 140

Width (mm): 30

High (mm): 6,5

Voltage In (Vac): 120

Intensidad In (A): 0.037

Frecuency (Hz): 50~60

Power (W): 4.5

Temperature (°C): -40+85

Room Temperature (°C): -40~+85

Critical Temperature (°C): 65

Colour Temperature (°K): 3000

Lumen: 450

Angle (°): 120

CRI (≥): 80

Life (Hours): 50000

Dimmable: SI

Power factor: >0.99

DOCUMENTS



[Data Sheet](#)