

G503520E

LED Power Supply CC Dimmable 0/1-10V SLD20-500ILA-UN1 up to 500mA 20W

May 25th, 2024, 09:10



DESCRIPTION

Led power supply for independant use 1-100% dimmable with 0 / 1-10V signal. Class II. Constant multi-current output from 150 to 500mA per dip-switch. Output voltage from 20 to 48 Vdc (150-300mA) and 8-40Vdc (350 to500mA). Power range 6-20W according to current selection. 85% efficiency. Protection against open circuit, short circuit and overload. Automatic reset in case of failure. Very low ripple current throughout the regulation range. Warranty 5 years.

PRICE

| Lot | P.V.P. excluding VAT |
|-----|----------------------|
| 1 | 32,46€ |
| 5 | 29,51€ |
| 10 | 26,83€ |
| 100 | 25,08€ |

Continued on next page >>

G503520E

LED Power Supply CC Dimmable 0/1-10V SLD20-500ILA-UN1 up to 500mA 20W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 124 Grams

Packging: Box 1 Unit

NOTES

ECO Design ERP Compliant. Dimmable 1-100% with 0 / 1-10V signal. Multi-current output 150-500mA dip-switch.

OTHER FEATURES

Length (mm): 103,1

High (mm): 22

Voltage In (Vac): 110~277

Intensidad Out (A): 0.15~0.5

Power (W): 2.8~20

Critical Temperature (°C): 85

Ingress Protection: IP20

Power factor: 0.95

Width (mm): 41

Colour: White

Voltage Out (Vdc): 20~40

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Life (Hours): 50000

Dimmable: 0-10V

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CC Dimmable 0/1-10V SLD20-500ILA-UN1 up to 500mA 20W](#)

 [CE](#)

 [C UR U.S. \(USA-Canada\)](#)

 [MEEI \(Hungary\)](#)