

LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers Control led mirrors

G5030060F

Led Power Supply CV AED60-12VIP44-3A-Q3 12V 60W

May 18th, 2024, 21:07



DESCRIPTION

Slimline Led power supply for independent use with constant voltage output. IP44 protection. Primary wiring with 15cm 2x1mm2 round hose cable for connection to the network and for the anti-fog. Three 15cm single-pole cables. in secondary + c-w-. On the back it has 3 sensors to be placed directly on the back of the mirror. Integrated Relay for demister. Ease installation and cost savings. Sensor 1. On/Off anti-fog function; Sensor 2. dimmer function; Sensor 3 CTT.

PRICE

| Lot | P.V.P. excluding VAT |
|-----|----------------------|
| 1 | 33,49€ |
| 5 | 27,91€ |
| 10 | 25,38€ |
| 100 | 23,71€ |

Continued on next page >>



LED TECHNOLOGY > Electronic Led Power Supplies > Led Controllers Control led mirrors

G5030060F

Led Power Supply CV AED60-12VIP44-3A-Q3 12V 60W

TECHNICAL SPECIFICATIONS



Weight: 800 Grams

NOTES

Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.

OTHER FEATURES

| Length (mm): 228,2 | Width (mm): 126,2 |
|-------------------------------|--------------------------------|
| High (mm): 18 | Colour: White |
| Voltage In (Vac): 220~240 | Voltage Out (Vdc): 12 |
| Intensidad Out (A): 5 | Frecuency (Hz): 50~60 |
| Power (W): 60 | Room Temperature (°C): -20~+40 |
| Critical Temperature (°C): 90 | Life (Hours): 30000 |
| Ingress Protection: IP44 | Dimmable: SI |
| Power factor: 0.90 | |

DOCUMENTS

Data Sheet

Led Power Supply CV AED60-12VIP44-3A-Q3 12V 60W

Electromagnetic compatibility