

Catalogue LED TECHNOLOGY
Line **Electronic Led Power Supplies**
FAmily **LED power supplies current and voltage constant**
Subfamily **Led power supplies current and voltage constant 350mA**

Picture	Article	Description	Lot	Price/Unit
	G503504A Led Power Supply CV CC AED04-350ILS 12Vdc 350mA 4W	ECO Design ERP Compliant. 12Vdc constant voltage LED power supply or 350mA constant current depending on load	1 10 50 200	5,57 € 4,63 € 4,21 € 3,93 €
		Length (mm): 51,5 Width (mm): 33 High (mm): 17 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~12 Intensidad Out (A): 0.3 Frecuency (Hz): 50~60 Power (W): 1.05~4.2 Room Temperature (°C): -10~+45 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5		

LETARON


LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies current and voltage constant

Subfamily **Led power supplies current and voltage constant 350mA**

Picture	Article	Description	Lot	Price/Unit
	G503506J Led power supply CV CC SLT6-350IL-4 350mA (24Vdc) 6W	Constant voltage 24VDC and constant current 350mA as identified by the load. Voltage range 100-240/24VDC. Class II.	1 5 10 50	9,82 € 8,19 € 7,44 € 6,90 €
		Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~22 Intensidad Out (A): 0~0.35 Frecuency (Hz): 50~60 Power (W): 6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 75 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0,40		



	G5035081 Led Power Supply CV CC 350mA (24VDC) 8 W Power supply 24VDC or constant current 350mA depending on load	1 5 10 50	11,33 € 9,44 € 8,59 € 8,02 €
	Length (mm): 58 Width (mm): 35 High (mm): 21 Colour: White Voltage In (Vac): 110~240 Voltage Out (Vdc): 3~24 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 1.1~8.4 Room Temperature (°C): -25~+50 Critical Temperature (°C): 75 Ingress Protection: IP20 Dimmable: NO Power factor: 0.6		

Reference: 039121



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies current and voltage constant

Subfamily Led power supplies current and voltage constant 350mA

Picture	Article	Description	Lot	Price/Unit
	G5035081A Led Power Supply CV CC AED08-350ILS 24Vdc 350mA 8 W	ECO Design ERP Compliant. 24Vdc constant voltage LED power supply or 350mA constant current depending on load	1 10 50 200	7,48 € 6,23 € 5,66 € 5,29 €
		Length (mm): 79,5 Width (mm): 39 High (mm): 19 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 9~22 Intensidad Out (A): 0.35 Frecuency (Hz): 50~60 Power (W): 3~7.7 Room Temperature (°C): -20~+45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5		

LETARON



Catalogue LED TECHNOLOGY
Line **Electronic Led Power Supplies**
Family **LED power supplies current and voltage constant**
Subfamily **Led power supplies current and voltage constant 700mA**

Picture	Article	Description	Lot	Price/Unit
	G503504C		1	5,57 €
	Led Power Supply CV CC AED04-700ILS 5Vdc		10	4,63 €
	700mA 3,5W		50	4,21 €
		ECO Design ERP Compliant. LED power supply with constant voltage 5Vdc or constant current 700mA depending on load	200	3,93 €
		Length (mm): 51,5 Width (mm): 32,8 High (mm): 17 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~5 Intensidad Out (A): 0.7 Frequency (Hz): 50~60 Power (W): 2~3.5 Room Temperature (°C): +45 Critical Temperature (°C): 80 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5		

LETARON



LED TECHNOLOGY > Electronic Led Power Supplies > LED power supplies current and voltage constant

Subfamily Led power supplies current and voltage constant 700mA

Picture	Article	Description	Lot	Price/Unit
	G503706C Led Power Supply CV CC 700mA (12Vdc) 6W	Length (mm): 42,5 Width (mm): 41 High (mm): 21 Colour: White Voltage In (Vac): 220~240 Voltage Out (Vdc): 12 Intensidad Out (A): 0.7 Frequency (Hz): 50~60 Power (W): 0~6 Room Temperature (°C): -20~+50 Critical Temperature (°C): 85 Ingress Protection: IP20 Dimmable: NO Power factor: 0.6	1 5 10 50	15,04 € 12,52 € 11,40 € 10,65 €
		Reference: 401244		

 ardeti
LUMINOSA INNOVACION
   

G503706H LED Power Supply CV CC SLT6-700ISC-UN 700mA (12Vdc) 6W	1 5 20 200	9,06 € 7,56 € 6,87 € 6,42 €
Constant voltage 12VDC and constant current 700mA as identified by the load. Voltage range 120-240 / 12VDC. Class II. Power factor: 0.90 @ 120V		
Length (mm): 52 Width (mm): 30 High (mm): 23 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 2.7~9 Intensidad Out (A): 0.7 Frequency (Hz): 50~60 Power (W): 2~6.3 Room Temperature (°C): -20~+45 Critical Temperature (°C): 90 Ingress Protection: IP66 Power factor: 0.80		

 SEIF
     

Subfamily **Led power supplies current and voltage constant 700mA**

Picture	Article	Description	Lot	Price/Unit
	G503706J LED power supply CV CC SLT6-700IL-4 700mA (12Vdc) 6W	 ECO design according to ERP directives. Led Power supply voltage 12VDC or constant current 700mA depending on load Length (mm): 68 Width (mm): 35 High (mm): 20 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 3~8.4 Intensidad Out (A): 0~0.7 Frequency (Hz): 50~60 Power (W): 6 Room Temperature (°C): -20~+40 Critical Temperature (°C): 70 Life (Hours): 50000 Ingress Protection: IP20 Dimmable: NO Power factor: 0,40	1 5 10 50	9,82 € 8,19 € 7,44 € 6,90 €

SELF

	G5035081B Led Power Supply CV CC AED08-700ILS 12Vdc 700mA 8 W	 ECO Design ERP Compliant. 12Vdc constant voltage LED power supply or 700mA constant current depending on load. Length (mm): 79,5 Width (mm): 39 High (mm): 19 Colour: White Voltage In (Vac): 100~240 Voltage Out (Vdc): 6~11 Intensidad Out (A): 0,625 Frequency (Hz): 50~60 Power (W): 4.2~7.7 Room Temperature (°C): -10~+45 Critical Temperature (°C): 80 Life (Hours): 30000 Ingress Protection: IP20 Dimmable: NO Power factor: 0.5	1 10 50 200	7,48 € 6,23 € 5,66 € 5,29 €
---	---	---	----------------------	--------------------------------------

LEΤΑΡΟΝ