

CACB2035ERM54

Coil 50m. Textile cable Low Voltage Graphite and black vertigo ERM54

May 09th, 2024, 19:24



DESCRIPTION

Flexible bipolar cable insulated with white silicone and inner cables 2x0.35mm2 of black and red rubber. Outside diameter 4mm. Suitable for LED applications with a voltage lower than 48V. The cable is ideal for class III mobile luminaires and for class II fixed installation luminaires with a nominal current not exceeding 2A. Nominal voltage 300 / 500V. Test voltage 2kV IEC EN 60228 Class 5. IEC EN 60754-1 / 2. IMPORTANT: Not suitable for mains voltage.

PRICE

| | Lot | P.V.P. excluding VAT |
|--|-----|----------------------|
| | 1 | 94,14€ |
| | 3 | 89,67€ |
| | 6 | 85,39€ |



Continued on next page >>

ELECTRICAL EQUIPMENT > Textile Cable and accessories > Low Voltage 48V Textile cable
Low Voltage 48V Textile cable 2x0.35mm²

CACB2035ERM54

Coil 50m. Textile cable Low Voltage Graphite and black vertigo ERM54

TECHNICAL SPECIFICATIONS

Weight: 1.09 Kilograms

Packging: Roll 50 Meters

NOTES

48V low voltage flexible bipolar cable insulated with white silicone and 2 copper conductors covered with black and red rubber with a section of 0.35mm², not suitable for mains voltage.
Diameter 4mm.

OTHER FEATURES

Section (mm²): 0,35

Voltage In (V): 300~500