

SMART LIGHTING > Lighting control by Nexta Tech > Receivers Constant current control, Dimmer, RGB

15TOPA0509EXT3

Control unit dimmer slave TOP-A0509/EXT3 for led CC 500-900mA



DESCRIPTION

Slave receiver control unit with dimmer function for control, via 433.92MHz radio or with cable via standard pushbutton, of LED power supplies with constant current of 500mA or 900mA selectable by jumper. For LED modules with constant current. With 3 outputs. Possibility to connect up to 4 slaves (extend) allowing to synchronize high powers. With 3 cable entries for standard push buttons. Wide and precise regulation and gradual rise and fall time (FADE) adjustable from 0 to 10 seconds. Simple programming through display. Its reduced dimensions allow its installation in the false ceiling or junction boxes.

PRICE

Lot	P.V.P. excluding VAT
1	60,66€
10	57,78€

Continued on next page >>



SMART LIGHTING > Lighting control by Nexta Tech > Receivers Constant current control, Dimmer, RGB

15TOPA0509EXT3

Control unit dimmer slave TOP-A0509/EXT3 for led CC 500-900mA

TECHNICAL SPECIFICATIONS

SYMBOLS

CERTIFICADOS

CE





Weight: 190 Grams

NOTES

Slave intensity regulator for LED modules with constant current at 500mA or 900mA selectable with jumper. Power supply with special cable for master-extender connection

OTHER FEATURES

Length (mm): 174

High (mm): 35

Ingress Protection: IP20

Width (mm): 46 Voltage In (Vdc): 12~36

DOCUMENTS

Mounting instructions