

G503540E

Led driver CC V8 350mA 40W

May 02nd, 2024, 00:30



DESCRIPTION

Led power supply for independent use at constant current 350mA. The output voltage goes from 57 to 114Vdc and the power range is from 20 to 40W. Class II. Screw terminals for cables from 0.75 to 2.5mm² section. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure.

PRICE

	Lot	P.V.P. excluding VAT
	1	10,24€
	5	8,53€
	10	7,75€
	50	7,23€

Continued on next page >>

LED TECHNOLOGY > Electronic Led Power Supplies > LED Power Supplies Constant Current
Electronic Led Power Supplies 350mA

G503540E

Led driver CC V8 350mA 40W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



CB



**UK
CA**



Weight: 125 Grams

NOTES

ECO Design ERP Compliant. 350mA constant current output

OTHER FEATURES

Length (mm): 127

High (mm): 28

Voltage In (Vac): 220~240

Intensidad In (A): 0.23

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Life (Hours): 30000

Dimmable: NO

Width (mm): 43

Colour: White

Voltage Out (Vdc): 57~114

Intensidad Out (A): 0.35

Power (W): 20~40

Critical Temperature (°C): 80

Ingress Protection: IP20

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [Led driver CC V8 350mA 40W](#)

 [ROHS](#)

 [CB](#)

 [EMC TUV CERTIFIED](#)

 [Safety TUV CERTIFIED](#)