

G5038040A

Led Power Supply CC LFM-40L multi-current 40W

May 02nd, 2024, 14:07



DESCRIPTION

Linear Led feeder to incorporate in class I with constant current output configurable with Dip-switch from 350A (42-58Vdc) to 700mA (42-58Vdc). Protection against open circuit, short circuit, overload and over temperature. Automatic reset in case of failure.

PRICE

	Lot	P.V.P. excluding VAT
	1	10,84€
	5	9,86€
	10	8,97€
	50	8,37€

Continued on next page >>

G5038040A

Led Power Supply CC LFM-40L multi-current 40W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 170 Grams

Packging: Box 1 Unit

NOTES

ECO ERP Design. Constant multicurrent output from 350mA to 700mA.

OTHER FEATURES

Length (mm): 280

Width (mm): 30

High (mm): 17

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 42~58

Intensidad Out (A): 0.35~0.7

Frecuency (Hz): 50~60

Power (W): 20~40

Room Temperature (°C): -20~+50

Critical Temperature (°C): 85

Ingress Protection: IP20

Dimmable: NO

Power factor: 0.95

DOCUMENTS



[Data Sheet](#)