

G5031020A

Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W

May 05th, 2024, 21:02



LETARON

DESCRIPTION

Slimline Led power supply for independent use with constant voltage output. IP44 protection. Primary wiring with 15cm 2x1mm² round hose cable for connection to the network and for the anti-fog. Three 15cm single-pole cables. in secondary + c-w-. On the back it has 3 sensors to be placed directly on the back of the mirror. Integrated Relay for demister. Ease installation and cost savings. Sensor 1. On/Off anti-fog function; Sensor 2. dimmer function; Sensor 3 CTT.

PRICE

	Lot	P.V.P. excluding VAT
	1	19,48€
	5	16,24€
	10	14,77€
	100	13,80€

Continued on next page >>

G5031020A

Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W

TECHNICAL SPECIFICATIONS

SYMBOLS

CERTIFICADOS



SELV



(EMC)



Weight: 800 Grams

NOTES

Integrated relais. Includes anti-fog, dimmer and CTT sensors for mirrors. Primary and secondary wiring.

OTHER FEATURES

Length (mm): 228,2

Width (mm): 126,2

High (mm): 18

Colour: White

Voltage In (Vac): 220~240

Voltage Out (Vdc): 24

Intensidad Out (A): 0.83

Frecuency (Hz): 50~60

Power (W): 20

Room Temperature (°C): -20~+40

Critical Temperature (°C): 85

Life (Hours): 30000

Ingress Protection: IP44

Dimmable: SI

Power factor: 0.85

DOCUMENTS

 [Data Sheet](#)

 [Led Power Supply CV AED20-24VIP44-3A-Q3 24V 20W](#)

 [Electromagnetic compatibility](#)