

G5031100D

LED Power Supply CV SLT100-24VFC-UN IP67 24V 100W

May 11th, 2024, 22:16



DESCRIPTION

Led IP67 power supply for independent use with constant voltage output of 24Vdc. Metal housing. Wiring with 15cm tripolar hose at the entrance and bipolar at the exit. On <0.5sec. Consumption without load <0.5W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. ECO design according to ERP directives. Efficiency 92.5%. Guarantee 5 years. Meets EN60335 and can be used inside refrigerator or freezer

PRICE

Lot	P.V.P. excluding VAT
1	47,39€
5	43,08€
10	39,17€
50	36,62€



Continued on next page >>

G5031100D

LED Power Supply CV SLT100-24VFC-UN IP67 24V 100W

TECHNICAL SPECIFICATIONS

SYMBOLS



SELV



Weight: 230 Grams

Packging: Box 1 Unit

NOTES

Meets ECO Design ERP. Ultra-flat 16.5mm. 24Vdc constant voltage output. Efficiency 92%

OTHER FEATURES

Length (mm): 340

Width (mm): 30

High (mm): 16

Colour: White

Voltage In (Vac): 120~240

Voltage Out (Vdc): 24

Frecuency (Hz): 50~60

Power (W): 100

Room Temperature (°C): -20~+50

Critical Temperature (°C): 75

Ingress Protection: IP67

Dimmable: NO

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CV SLT100-24VFC-UN IP67 24V 100W](#)

 [CE](#)

 [MEEI \(Hungary\)](#)