

G5031030C

LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W

April 28th, 2024, 19:34



DESCRIPTION

Extra-flat IP67 LED power supply for independent use with 24Vdc constant voltage output. Metal casing. Wiring with 15cm tripolar hose at the inlet and bipolar at the outlet. On <0.5sec. Consumption without load <0.5W. Protection against open circuit, short circuit, over load and over temperature. Automatic reset in case of failure. ECO design according to ERP directives. 84.5% efficiency. 5-year warranty. Complies with EN60335 and can be used inside a refrigerator or freezer

PRICE

	Lot	P.V.P. excluding VAT
	1	33,05€
	5	30,04€
	10	27,31€
	50	25,52€

Continued on next page >>

G5031030C

LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W

TECHNICAL SPECIFICATIONS

SYMBOLS

SELV



RoHS
COMPLIANT

CE

UL US



Weight: 224 Grams

Packging: Box 1 Unit

NOTES

ECO Desogn ERP. IP67. Extra flat. Constant voltage output 24Vdc. Efficiency 84.5%

OTHER FEATURES

Length (mm): 275

High (mm): 16

Voltage In (Vac): 120~240

Intensidad Out (A): 0~1.25

Power (W): 0~30

Critical Temperature (°C): 75

Dimmable: NO

Width (mm): 30

Colour: Grey

Voltage Out (Vdc): 24

Frecuency (Hz): 50~60

Room Temperature (°C): -20~+50

Ingress Protection: IP67

Power factor: 0.95

DOCUMENTS

 [Data Sheet](#)

 [LED Power Supply CV SLT30-24VFC-UN IP67 24V 30W](#)

 [CE](#)

 [MEEI \(Hungary\)](#)

 [Regulatory Compliance Mark for Australia](#)