

G5K000P02

Mini control board D40 module led to battery GPC02

April 30th, 2024, 03:53



DESCRIPTION

Fiberglass plate in circular shape. Outer diameter 40mm. With 4 fixing holes of 3mm diameter. The plate has a Jumper controller that allows you to choose the luminous flux at 150lm or 250lm. Connectors for 1 or 2 batteries. If only a battery is put in the other connector is free. The battery can be connected indistinctly to any of the 2 connectors and must be connected after connecting the touch control .. Depending on the luminous flux selected, you can choose to put one or two batteries depending on the necessary time of autonomy. Connector for touch control and to the micro USB. Independent connectors + and - for the led plate. Optional RF connector for remote control control.

PRICE

	Lot	P.V.P. excluding VAT
	1	10,48€
	10	9,53€
	50	8,66€
	150	8,25€



LED TECHNOLOGY > Led modules > Battery Led Modules
Configurable Led battery modules

G5K000P02

Mini control board D40 module led to battery GPC02

TECHNICAL SPECIFICATIONS

SYMBOLS



CERTIFICADOS



Weight: 7 Grams

Packging: Box 1 Unit

NOTES

Jumper that allows you to choose 150lm or 250lm. Connectors with 1 or 2 batteries, touch and micro USB.

OTHER FEATURES

High (mm): 10

Diameter (mm): 40

Ingress Protection: IP20

Dimmable: SI

DOCUMENTS

 [Data Sheet](#)

 [CE](#)